Lumera D

ORT-LED95D

Patented design



CE CB IP65 IK08

Technical information


Parameter	Technical data	Parameter	Technical data
Lifetime	Up to 100,000hrs LM70,Ta 25℃	Driver isolation	Class I or Class II
Wattages	30~50W	Control dimming	DALI / 1-10V / Timing / PWM
Light efficacy	Up to 130lm/W	Operating temperature	-35℃~50℃ / 10% ~ 95% (humidity)
CRI	≥ 70 or ≥ 80	Body parts material	Die cast Aluminum
Color temperature	3000K, 4000K, Amber color	Optic	PC (standard)
Operation voltage	AC 90-305V or AC 220-240V	Screen	PC
Frequency	50 / 60Hz	Gasket	Silicone
Power factor	≥0.95 cos	Color stability	3 or 5 MacAdam steps

Parking lot Village Park Road

Optics available



5050	G11C36-T2	C12C36-T5
36*1		



Chip	LED QTY	Lens QTY	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
5050	24	1	30	3900	130
5050	30	1	40	5200	130
5050	36	1	50	6500	130

Base




PIR for Bollard

Infrared Motion Sensor



Code.20013001



5050: LUMILEDS 5050; 3535: CREE XPG3; 3030: LUMILEDS 3030

Lm: This data is tested under normal working condition, the actual data will depend on environment condition, optics/diffuser and CCT.