Lumera

ORT-LED95

Patented design

Parking lot Village Park Road

ø60mm





CE CB IP65 IK08

Accessories - Adapter




Stripe version



Module

Optics available










Technical information


Parameter	Technical data	Parameter	Technical data
Lifetime	Up to 100,000hrs LM70,Ta 25℃	Driver isolation	Class I or Class II
Wattages	30~50W	Control dimming	DALI / 1-10V / Timing / PWM
Light efficacy	Up to 130lm/W	Operating temperature	-35℃~50℃ / 10% ~ 95% (humidity)
CRI	≥ 70 or ≥ 80	Body parts material	Die cast Aluminum
Color temperature	3000K, 4000K, Amber color	Optic	PC (standard)
Operation voltage	AC 90-305V or AC 220-240V	Ball material	PC
Frequency	50 / 60Hz	Gasket	Silicone
Power factor	≥0.95 cos	Color stability	3 or 5 MacAdam steps





Chip	LED QTY	Lens QTY	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
5050	24	1	30	3900	130
5050	30	1	40	5200	130
5050	36	1	50	6500	130

Packing Information

Model	Carton Size (L*W*H)	QTY/Carton	N.W.(kg)	G.W.(kg)
ORT-LED95	435*435*530mm	1	4.9	6.9







5050: LUMILEDS 5050; 3535: CREE XPG3; 3030: LUMILEDS 3030
Lm: This data is tested under normal working condition, the actual data will depend on environment condition, optics/diffuser and CCT.