ORYX LIGHTING



SOLVEX

NEW

Solvex NEW

ORSS-LED01 Series

Patented design



CE IP65 IK08

Details



Optics available




Technical information

Parameter	Technical data	Parameter	Technical data
LED Lifetime	Up to 50,000hrs LM70,Ta 50℃	Control dimming	Timing
Wattages	30W	Operating temperature	-20℃~60℃ / 10% ~ 95% (humidity)
Light efficacy	Up to 180 lm/W	Body parts material	ADC12 (standard) / LM6 (option)
CRI	≥ 70 or ≥ 80	Optic	PC (standard) / PMMA (option)
Color temperature	3000K, 4000K, Amber color	Screen	Flat tempered glass 5mm thickness
Operation voltage	DC 24V	Gasket	Silicone
Color stability	3 or 5 MacAdam steps		

Packing Information

Model	Carton Size (L*W*H)	QTY/Carton	N.W.(kg)	G.W.(kg)
ORSS-LED01S	915*385*170 mm	1	17.1	18.1



Model	Chip	LED QTY	Power (W)	Current (mA)	Luminaire efficacy (lm/W)	Working mode	Autonomy Information	LifePO4 Battery
ORSS-LED01	5050	48	30	1250	180	2hrs-100%, 2hrs-60%, 6hrs-30%, 1hrs-100%	2days	461WH/12 .8V 36AH

