Vector C

ORXCP-2001S

Patented design



IP65 IK09

Technical information

Parameter	Technical data	Parameter	Technical data
Insulation class	Class I / Class II	Screen	PC
Operating temperature	-20℃~50℃ / 10% ~ 95% (humidity)	Gasket	Silicone
Body parts material	Aluminum	Color stability	5 MacAdam steps
Light control	Optic / Diffuser	IP & IK Rating	IP65 & IK09


Packing Information

Model	Outer Carton Size (L*W*H)	QTY/ Outer Carton	N.W.(kg)	G.W.(kg)
ORXCP-2001S-40	420*210*190mm	1	2.6	3
ORXCP-2001S-60	620*210*190mm	1	3.4	4
ORXCP-2001S-90	920*210*190mm	1	4.4	5.2

Other option



Solar solution (optional)




ORXCP-2001S-40

CCT	CRI	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Input voltage	Dimming
3000K	>80	12	1020	85	AC 220-240V	ON/OFF

Solar Solution Order

CCT	CRI	LED Power (W)	Lumen (lm)	Solar panel power	Battery Voltage	Sensor
3000 K	>80	3V 5W	240	5V 3W	3.7V Lithium battery	Infra-red sensor




ORXCP-2001S-60

CCT	CRI	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Input voltage	Dimming
3000K	>80	12	1020	85	AC 220-240V	ON/OFF

Solar Solution Order

CCT	CRI	LED Power (W)	Lumen (lm)	Solar panel power	Battery Voltage	Sensor
3000 K	>80	3V 5W	240	5V 3W	3.7V Lithium battery	Infra-red sensor



ORXCP-2001S-90

CCT	CRI	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)	Input voltage	Dimming
3000K	>80	12	1020	85	AC 220-240V	ON/OFF

Solar Solution Order

CCT	CRI	LED Power (W)	Lumen (lm)	Solar panel power	Battery Voltage	Sensor
3000 K	>80	3V 5W	240	5V 3W	3.7V Lithium battery	Infra-red sensor

Lm: This data is tested under normal working condition, the actual data will depend on environment condition, optics/diffuser and CCT.