Virex

Parking lot Village Park Road

ORGKD-LED02 Series

Patented design

THREE SIZE

HYGKD-LED02




Optics available



3030	90°	120°
		

Options






CE IP65 IK09

Technical information

Parameter	Technical data	Parameter	Technical data
Lifetime	Up to 100,000hrs LM70,Ta 25℃	Driver isolation	Class I
Wattages	100~200W	Control dimming	1-10V / Timing / PWM
Light efficacy	Up to 120 lm/W	Operating temperature	-35℃~50℃ / 10% ~ 95% (humidity)
CRI	≥ 70 or ≥ 80	Body parts material	Die cast Aluminum
Color temperature	3000K, 4000K, 6500K	Optic	PC (standard)
Operation voltage	AC 100-256V	Screen	PC
Frequency	50 / 60Hz	Gasket	Silicone
Power factor	≥0.95 cos	Color stability	3 or 5 MacAdam steps

Packing Information

Model	Carton Size (L*W*H)	QTY/ Carton	N.W. (kg)	G.W. (kg)
ORGKD-LED02-S	270*110*272mm	1	1.5	2.4
ORGKD-LED02-M	320*105*322mm	1	2.0	3.1
ORGKD-LED02-L	355*115*357mm	1	2.6	3.8



ORGKD-LED02-S



Φ260

Chip	LED QTY	Lens QTY	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
3030	141	1	100	10000	100

ORGKD-LED02-M



Φ310

Chip	LED QTY	Lens QTY	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
3030	198	1	150	15000	100

ORGKD-LED02-L



Φ345

Chip	LED QTY	Lens QTY	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
3030	282	1	200	20000	100

3030: LUMILEDS 3030
Lm: This data is tested under normal working condition, the actual data will depend on environment condition, optics/diffuser and CCT.